

Features

- Suitable for receptacles or against insulated wire
- Double insulated housing for increased safety
- Audible (buzzer) and visual (LED) indicators
- Built-in flashlight
- Pocket clip
- Auto shut off
- Cat. IV 1000V safety rating
- Includes batteries

Specifications

| | |
|--------------------------------|---------------------------------------|
| Voltage Range: | Low Voltage Mode: 24 to 1000VAC |
| | High Voltage Mode: 90 to 1000VAC |
| Frequency Range: | 50 to 60Hz |
| Built-in Flashlight: | Yes |
| Pocket Clip: | Yes |
| Alarm: | Yes (audio/visual) |
| Auto Shut-off: | Yes (after 5 mins) |
| Low Battery Indicator: | Yes |
| Power Supply: | 2 x AAA Batteries |
| Oversvoltage Category: | CAT. IV 1000V |
| Product Certifications: | CE, ETL |
| Operating Temperature: | 32 to 104°F (0 to 40°C) |
| Storage Temperature: | -4 to 122°F (-20 to 50°C) |
| Operating Humidity Range: | 0 to 80% |
| Maximum Operating Altitude: | 6561' (2000m) |
| Dimensions: | 5.9 x 0.9 x 0.7" (150 x 23 x 18mm) |
| Weight: | 1.8oz (50g) |

TECHNICAL DATA



| Model | Description |
|------------|---|
| R5110 | Non-Contact Voltage Detector with Flashlight |
| R5110-10PK | Non-Contact Voltage Detector with Flashlight, 10-Pack |